




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: A62B 3/00, A62C 8/08, E06B 5/16	A1	(11) International Publication Number: WO 98/09681 (43) International Publication Date: 12 March 1998 (12.03.98)
(21) International Application Number: PCT/NO97/00234 (22) International Filing Date: 4 September 1997 (04.09.97) (30) Priority Data: 963717 6 September 1996 (06.09.96) NO (71)(72) Applicant and Inventor: BURMO, Odd, Gunnar [NO/NO]; Grønlundv. 1, N-2022 Gjerdrum (NO).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>With amended claims.</i> <i>In English translation (filed in Norwegian).</i>

(54) Title: COMBINED FIREDRAUGHT BARRIER, FIRE SHIELD AND FIRE HOSE BASE

(57) Abstract

The combined firedraught barrier, fire shield and fire hose base comprises an easy-to-handle, portable formed plate (1) having a crossbar (2), a window (3), centre openings (4) for nozzles, and openings (6) at floor level for fire hoses, for fire-fighting from door and window openings and for stopping the inflow of oxygen. The plate serves as a fire shield, firedraught barrier and fire hose base, and also be as a door for smoke divers. At the top of the plate one or more smoke valves are provided for ventilation to allow the heat of the fire to escape. The fireman can stand behind the plate with one foot on the footboard (5) and hold the plate against the door frame to stop the firedraught/inflow of oxygen. At the same time, the fireman can fight the fire by using a nozzle through the centre opening (4). A window (3) in the plate may provide some visibility. Openings (6) in the plate at floor level are intended for fire hoses which may pulled along the floor into the interior of e.g., a building, by smoke divers.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

COMBINED FIREDRAUGHT BARRIER, FIRE SHIELD AND FIRE HOSE BASE

Description

The present invention relates to a combined firedraught barrier, fire shield and fire hose
5 base, which firemen can easily carry to the scene of a fire, and use both as a fire shield and
fire-fighting equipment in extinguishing the fire. The invention can be used for both doors
and windows. The background for the term "firedraught barrier" is that in a house fire the
inflow of oxygen takes place at floor level through, e.g., an open door, and the intention is
to prevent this inflow of oxygen.

10

Experience has shown that all too often fires, which were about to die out due to oxygen
starvation, have flared up and caused a great deal of unnecessary damage after firefighters
have started to extinguish the fire through open doors. The inflow of oxygen (firedraught)
has been able to flow freely to the fire. There are numerous examples of houses totally
15 destroyed by fire, even though there was no sign of flames when fire-fighting commenced.
The inflow of oxygen has then caused the fire to blaze up.

A type of gas-lock in the form of a tent designed to be placed in front of doors has
previously been proposed in NO Application 924375, but this has not become a marketable
20 product.

When using the firedraught barrier, it is possible to open a door without causing a fire on
the inside of the door, which is giving off only or mostly smoke and fumes, to burst into
flames by placing the firedraught barrier in the door opening and against the door frame as
25 soon as the door is opened. The invention will prevent the inflow of oxygen and will also
function well as a portable fire shield and fire hose base.

At the bottom of the invention there are openings for fire hoses which can be pulled along
the floor into the building. There is also an opening in the centre of the invention through
30 which the nozzle of a fire hose can be projected. The nozzle can be placed on a support
extending from the centre opening to a crossbar for handling the invention, so that the user
can save energy whilst handling the fire hose.

The fact that the invention is curved inwards at the centre allows it to be suitably
35 positioned in door opening for fire-fighting. The invention can be held in place by the
pressure of the user's foot on a footboard at the bottom of the invention. Pressure from the
weight of the fire hose on the crossbar will also help to hold the invention against the door
frame.

40 The invention can be manoeuvred and controlled by handling a crossbar, if, for example, a smoke diver is to enter the building or room. The smoke diver can then squeeze in and out on one side or the other with a minimum opening. The smoke diver can pull a fire hose in through one of the openings at floor level, so that unnecessary inflow of oxygen is prevented. Depending upon visibility, the operator of the invention can observe the fire
45 through a window located above the centre opening.

A fire inside a building will create a great deal of smoke and fumes and an elevated inside air pressure. To release the heat of the fire, there is a single hanging smoke valve at the top of the invention. The smoke valve will remain open as long as the air pressure inside is
50 higher than outside. The smoke valve will gradually close to prevent inflow of oxygen.

Some form of ventilation equipment may conceivably be coupled to the smoke valve to permit greater control of the smoke if it is desirable to lead the smoke and fumes to a location other than just outside the door.

55

In real life it is not difficult to observe the inflow of oxygen through the lower part of e.g., a door, and the outflow of hot smoke from inside through the upper part.

Firemen have used this phenomenon to inject fog at floor level, but the drawback is that the inflow of oxygen sustains the fire. The invention will make it possible to stand in a door
60 opening, protected against heat radiation, whilst using fire hoses to fight the fire. At the same time, the firemen will also have control of the inflow of oxygen, which is something they do not have today.

The novelty of the invention resides in the absence of a tight-fitting solution for doors and
65 windows, and the combination of firedraught barrier, safety equipment and fire hose base.

The invention can be made of several types of material, but is preferably made of a suitable lightweight material that is easy to handle and can stand 1000 - 1300 degrees Celsius, and which is functional.

70

The combined firedraught barrier, fire shield and fire hose base according to the invention is illustrated in the drawings.

Fig. 1 is a side view from above of the inside of the invention. The openings (6) should
80 preferably have easy-to-handle, closeable flaps or the like. The centre opening (4) has a support (8) for nozzles extending from the opening (4) to a crossbar (2). On the edge of

the support it is preferable to have a stopper for the nozzle. When in use, the nozzle must be capable of being pointed forward in any direction.

85

Fig. 2 is a side view of the firedraught barrier set up for use in a door opening, and where it is possible to see a fire hose and an open smoke valve (7) for ventilation to allow the escape of the smoke flow.

90 Fig. 3 is a view of the rear of the window version, wherein there are two openings for nozzles. This version can be nailed in place in front of a window to prevent inflow of oxygen.

Fig. 4 is a view of the firedraught barrier set up for use in a door opening, and where it is
95 possible to see the ventilation equipment, consisting of a couplingbox (9) in connection with a smoke hose / pipe (10), to lead the smoke and fumes to a location other than just outside the door.

The description and drawings are to be understood thus that the disclosed embodiments
100 are merely exemplary of the invention, which may be embodied in various forms.

Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims.

1 PATENT CLAIMS

1.

A portable, combined firedraught barrier, fire shield and fire hose base for fire-fighting.

5 The door version is characterised in that an easy-to-handle, portable formed plate (1) having a crossbar (2), a window (3), one or more openings (4) for nozzles, openings (6) at the bottom for fire hoses, a footboard (5) and one or more smoke valves (7) for ventilation, is used as a fire shield and a fire hose base to prevent the inflow of oxygen through, e.g., a door opening.

10 The window version does not have the footboard (5).

The novelty of the invention resides in the combination of firedraught barrier, safety equipment and fire hose base.

2.

15 The invention according to claim 1, characterised in that the formed plate (1) is curved inwards in the case of the door version.

3.

20 The invention according to claim 1, characterised in that the openings (6) for fire hoses are easily closeable.

AMENDED CLAIMS

[received by the International Bureau on 14 January 1998 (14.01.98);
original claim 1 amended; new claim 4 added; remaining claims
unchanged (1 page)]

1.

A portable, combined firedraught barrier, fire shield and fire hose base for fire-fighting. The door version is characterised in that an easy-to-handle, portable formed plate (1) having a crossbar (2), a window (3), one or more openings (4) for nozzles, openings (6) at the bottom for fire hoses, a footboard (5) and one or more smoke valves (7) for ventilation, a support (8) for nozzles extending from the centre opening (4) to a crossbar (2), is used as a fire shield and a fire hose base to prevent the inflow of oxygen through, e.g., a door opening.

2.




The invention according to claim 1, characterised in that the formed plate (1) is curved inwards in the case of the door version.

3.

The invention according to claim 1, characterised in that the openings (6) for fire hoses are easily closeable.

4.

The invention according to claim 1, have one or more smoke valves (7) with a coupling for ventilation equipment. This ventilation equipment consist of a couplingbox (9) in connection with a smoke hose / pipe (10), to lead the smoke and fumes to a location other than just outside the door.



INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 97/00234

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A62B 3/00, A62C 8/08, E06B 5/16
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: E06B, A62C, A62B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 336785 A (H. BURROWS ET AL), 23 October 1930 (23.10.30) ---	1-3
X	FR 44946 E (A. PUJES), 1 May 1935 (01.05.35) ---	1-3
A	CH 243740 C (ALUMINIUMWERKE AG), 16 January 1947 (16.01.47) ---	1-3
A	CH 281604 C (WALO, HOERNING), 1 July 1952 (01.07.52) ---	1-3

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

5 December 1997

Date of mailing of the international search report

08-12-1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Mariana Eddin
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 97/00234

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 3413182 A1 (LENHARD, LEO), 7 November 1985 (07.11.85) --	1-3
A	DE 3446551 A1 (LENHARD, LEO), 3 July 1986 (03.07.86) -- -----	1-3

INTERNATIONAL SEARCH REPORT
Information on patent family members

04/11/97

International application No.
PCT/NO 97/00234

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
GB	336785	A	23/10/30	NONE	
FR	44946	E	01/05/35	NONE	
CH	243740	C	16/01/47	NONE	
CH	281604	C	01/07/52	NONE	
DE	3413182	A1	07/11/85	DE 3446551 A	03/07/86
DE	3446551	A1	03/07/86	DE 3413182 A	07/11/85